

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2001-250580

(43)Date of publication of application : 14.09.2001

(51)Int.Cl.

H01M 10/36
C04B 35/547

(21)Application number : 2000-060119

(71)Applicant : TATSUMISUNA MASAHIRO


(22)Date of filing : 06.03.2000

(72)Inventor : TATSUMISUNA MASAHIRO
MORIMOTO HIDEYUKI
HAYASHI AKITOSHI
MINAMI TSUTOMU

(54) SULFIDE CERAMICS WITH HIGH LITHIUM ION CONDUCTIVITY AND ALL SOLID CELL USING THE SAME

(57)Abstract:

PROBLEM TO BE SOLVED: To provide sulfide ceramics of high lithium ion conductivity and decomposition voltage.

SOLUTION: The solid electrolyte for a lithium ion secondary cell is composed of Li₂S and P₂S₅ as a main component, where a crystalline sulfide in which Li₂S of mole % of 82.5-92.5 and P₂S₅ of mole % of 7.5-17.5 are comprised, shows a high lithium ion conductivity. Here, the higher-temperature stable phase shows very high lithium ion conductivity.

LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the
examiner's decision of rejection or application
converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of
rejection][Date of requesting appeal against examiner's decision
of rejection]

[Date of extinction of right]

Copyright (C); 1998,2000 Japan Patent Office